

CRUISE 2

MOBILE COMPUTERS

CRUISE 2

The New Generation of CRUISE Series



A new generation of CRUISE equipment has been introduced by Seuic, based on its star product "CRUISE1P" - CRUSIE2, which has many advantages in terms of performance, reliability, and operation experience compared to the first-generation CRUISE, with good grip and easy operation. In addition, many improvements have been made to offer the front-line employees a better operating experience and increase their efficiency.



Product Features



Strong core and performance

Qualcomm Snapdragon octa-core 2.0 GHz processor, running performance is 100% higher than the first generation of CRUISE so that a variety of applications can be used smoothly



high-speed Wi-Fi transmission

The latest Wi-Fi 6 ready technology, compared to the first generation, has significantly improved connection stability and transmission distance. In addition, despite dense three-dimensional shelving in large warehouses, it is smooth to connect for real-time data transmission.

Additional optional ex-range scanner which can reach 10m reading can enlarge the feasibility in warehouse and outdoor.

Specifications

Physical Characteris	
Dimensions	Standard battery model:
	6.1 in. L x 3 in. W x 0.5 in. H
	156 mm L x 76 mm W x 13.9 mm H
	6000mAh battery model:
	6.1 in. L x 3 in. W x 0.6 in. H
	156 mm L x 76 mm W x 16.4 mm H
Weight	9.0 oz./255 g (5000mAh model)
	9.8 oz./279 g (6000mAh model)
Display	5.5 in. color HD (720 x 1440)
Touch Panel	Capacitive touch, supporting wet hand mode and
	glove mode
Power	Detachable 5000mAh Li-ion rechargeable battery
	with hot-swap, optional 6000mAh
	40mAh Li-ion spare battery
Expansion Slot	Maximum compatible storage: 128GB
Interface/	Waterproof Type-C USB interface, supporting Type-C
Communication	earphone, USB2.0 Highspeed, OTG and fast charge
	Nano/TF card, card slot with two out of three
Notifications	Sound, vibrator, LED light indication
Fingerprint	Support
identification	
Keypad	Volume +/ - button, Power ON/OFF button, Left Scan
, p	button, Right Scan button, Custom button, Virtual
	On-Screen button (Return button, Home button,
	Menu button)
Voice and Audio	Speaker, dual microphones, PTT voice (Internal
voice and radio	speaker and Bluetooth wireless headset support)
Performance Chara	
CPU	Qualcomm Octa-core 2.0GHz
Operating System	Android 11, GMS with AER Certified
Memory	4GB RAM/64 GB Flash memory.
wiemory	6GB RAM/64 GB Flash memory (Optional)
User Environment	OGB NAME OF GB Hash memory (Optional)
	4°E to 131°E/ 30°C to JEE°C
Operating Temp.	-4 °F to 131 °F/-20 °C to +55 °C
Storage Temp.	Battery included: -40 °F to 158 °F/-40 °C to +70 °C
Humidity	5% to 95%, non-condensing
Drop Spec.	4.9 ft./1.5 m drops to concrete at room temperature
Tumble Spec.	1000 1.6 ft./ 0.5 m tumbles
Sealing	IP68
Electrostatic	±15 kV air discharge, ±8 kV direct discharge
Discharge (ESD)	
Sensor	G-sensor, light sensor, proximity sensor, electronic
	compass, gyroscope

Data Capture		
Scanning	Seuic 2D Barcode scanner	
	Honeywell N6803-FR	
	Camera scanning	
Camera	Front: 5 MP	
	Rear: 13 MP autofocus, flash LED with flashlight	
	mode	
NFC	Supports tags ISO15693, ISO14443A/B (without	
	encryption protocol), ISO14443A with encryption	
	protocol (Mifare One S50,S70 and compatible cards);	
	supports NFC Protocol	
Wireless Connectivity		
WLAN		
WLAN Radio	IEEE 802.11 a/b/g/n/ac/ax ready /d/e/h/i/k/r/v/w	
TT LT TT T	(2.4G/5G dual-band WIFI) protocol	
Working Channel	CH1~CH13, CH36-CH140, CH149~CH165	
Security of WLAN	Supports WPA2 –Personal, WPA2 –Enterprise,	
Security of WEAR	EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-	
	MSCHAPv2, PEAPv1/EAP-GTC, EAP-SIM, EAP-AKA,	
	EAP-AKA Prime	
WWAN	LAI -AIA I TIITE	
WWAN Radio	GSM:Qual Band(850/900/1800/1900Mhz)	
W WAIN RAUIO	TD-SCDMA: Band34, Band39	
	WCDMA: Band1, Band2, Band5, Band8	
	CDMA 1x /EVDO: BC0	
	TDD-LTE: Band34, Band38, Band39, Band40, Band41	
	FDD-LTE: Band1, Band3, Band5, Band7, Band8,	
	Band20, Band28	
GPS	GPS+GLONASS+ Beidou, Supporting AGPS	
Gra	GPS:L1(1.575GHz)+L5(1.176GHz);	
	Beidou:B1(1.561GHz); GLONASS: L1(1.602GHZ)	
WPAN	Deldod.D1(1.301G112), GEONASS. E1(1.502G112)	
Bluetooth	Bluetooth 5.1 (supports BLE)	
Accessories	Bidetooth 3.1 (supports BLL)	
Standard	Power Adapter(18W), USB Cable	
Additional	Protective cover (including hand strap), Single	
Additional	device charging cradle ,5-slot cradle, 4 batteries	
Third Party Applicat	charger, pistol grip	
Third Party Application Development Support		
System Software	Android 11	
System	Eclipse, Android Studio	
Programming		
Environment		





